Internal Sounders

Product Overview

The Inter range of internal sounders are designed for use in domestic applications and are available in three versions:

- High level sounder
- High (alarm) and low level (entry/exit) sounder with strobe
- High (alarm) and low level (entry/exit) sounder

They are also available with or without an internal battery for SAB or direct operation (see table).

The sound output for all models is 110dB(A). They have a low current consumption and feature engineer mode for silent start up.

The devices have a modern, stylish polycarbonate cover which can be screen printed with a company logo if required (not 500(S) model).

Features

- 12V dc operation
- Grade 2 & 3 options
- Environmental class II
- Tough polycarbonate cover and backplate
- Front and rear tamper
- Independent low level entry/exit sound output (500/600)
- Selectable 15m timer for sounder output
- Integral strobe (500)
- Selectable siren tomes (500/600)
- Screen printing available on all models except 500(S)
- 3 year warranty

Approvals & Certification

Inter sounders meet the requirements of:

- PD6662:2017
- EN50131-1:2006
- EN50131-4:2009



Internal Sounder Range

Part Numbers

| Part no | Grade | Strobe | Description |
|-----------|-------|--------|--|
| INT400 | 3 | | High level sounder |
| INT400(S) | 2 | N | High level sounder with NiCad battery for SAB operation |
| INT500 | 3 | | High & low level sounder with strobe |
| INT500(S) | 2 | Y | High & low level sounder with strobe and NiCad battery for SAB operation |
| INT600 | 3 | | High & low level sounder |
| INT600(S) | 2 | N | High & low level sounder with NiCad battery for SAB operation |

Technical Information

Full SAB option 6V NiCd (150mAh)

Sounder

Sound out (at 1m) 110dB(A)

Input voltage 10-14V dc (12V dc nom)

Standby Current 15mA

Strobe

Flash rate 1 per second

Input voltage 12V dc

Product Dimensions

H x W x D: 110mm x 160mm x 40mm











Elmdene International Limited 3 Keel Close, Interchange Park, Portsmouth, Hampshire, PO3 5QD, UK. Tel: +44 (0)23 9269 6638 Fax: +44 (0)23 9266 0483 Email: sales@elmdene.co.uk © 2019 Elmdene International Limited

Specifications subject to change without notice.