

# DECLARATION OF PERFORMANCE

DoP2014/0002

According to the Construction Products Regulation EU no. 305/2011

1	Unique Identification code of the product	STX2401-T
2	Type, batch or serial number or any other element allowing identification of the construction product	Products are provided a batch manufacturing code based on date format
3	Intended use or uses of the construction product	Battery backed up Power supply for Fire Detection, signaling and indication equipment
4	Name, registered trade name or registered trade mark and contact address of the manufacturer	Elmdene International Limited 3 Keel Close, Interchange Park, Portsmouth, PO3 5QD, UK
5	Where applicable, name and contact address of the authorised representative	Not applicable
6	System or systems of assessment and verification of constancy of performance	System 1 testing
7	Name and Identification of notified body	DBI Certification A/S, Jernholmen 12, 2650 Hvidovre. NB: 2531
	Date of compliance and continuing approval	18-12-2020
	Under System	Level 1 - Factory Production Control
	CPR EC Certificate	2531-CPR-CSP11212
8	In case of declaration of performance concerning a construction product for which European Technical Assessment has been issued	Not applicable.

## 9. Declared performance

Essential Characteristics	Performance	Standard
<b>Operational reliability</b>		
4 General Requirements	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
5 Functions	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
6 Materials, design and manufacture	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
7 Documentation	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
8 Marking	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
<b>Performance of Power Supply</b>		
4 General Requirements	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
5 Functions	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
6 Materials, design and manufacture	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
<b>Durability of operational reliability: temperature resistance</b>		
9.5 Cold (Operational)	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
<b>Durability of operational reliability: vibration resistance</b>		
9.7 Impact (operational)	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
9.8 Vibration, sinusoidal (operational)	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
9.15 Vibration, sinusoidal (endurance)	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
<b>Durability of operational reliability: electrical stability</b>		EN 54-4:1997 + A1:2002 + A2:2006
9.9 Electromagnetic Compatibility (EMC), Immunity Tests	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
<b>Durability of operational reliability: vibration resistance</b>		
9.7 Impact (operational)	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
<b>Durability of operational reliability: humidity resistance</b>		
9.6 Damp heat, steady state (operational)	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006
9.14 Damp heat, steady state (endurance)	<b>Pass</b>	EN 54-4:1997 + A1:2002 + A2:2006

10. The performance of the Product Identified in (1), (2) above, is in conformity with the declared performance in (9). This declaration of Performance is issued under the sole responsibility of the manufacturer identified in (4) For and on behalf of Elmdene International Ltd