

# **Elmdene International Ltd** 3 Keel Close, Interchange Park,

Portsmouth, Hampshire, PO3 5QD, UK

Tel: +44(0)23 9269 6638 ≞Fax: +44(0)23 9266 0483 Web: www.elmdene.co.uk

# SS2-X (Set Switch with LED)

### Overview


The set switch is designed to provide a means of setting an alarm system from a door bell push. An LED can be used to provide a visual indication of the control panel condition.


## Operation

The unit comprises a normally open push button switch and an LED to provide a visual indication rated for 12v DC.

### Specification

Length of front bezel	50 mm
Width of front bezel	28 mm
Depth behind bezel	12 mm
Operating Voltage (LED)	12v DC
Switching current	50mA
Switching current	JUIIA





Technical Support Line: +44 (0)23 9269 6638 (Option 3) © 2012 Elmdene International Ltd

PAK200072 Issue 02A August 2012



# **Elmdene International Ltd**

3 Keel Close, Interchange Park, Portsmouth, Hampshire, PO3 5QD, UK

Tel: +44(0)23 9269 6638 ≞Fax: +44(0)23 9266 0483 Web: www.elmdene.co.uk

## SS2-X (Set Switch with LED)

### Overview


The set switch is designed to provide a means of setting an alarm system from a door bell push. An LED can be used to provide a visual indication of the control panel condition.


## Operation

The unit comprises a normally open push button switch and an LED to provide a visual indication rated for 12v DC.

### Specification

Length of front bezel	50 mm
Width of front bezel	28 mm
Depth behind bezel	12 mm
Operating Voltage (LED)	12v DC
Switching current	50mA





Technical Support Line: +44 (0)23 9269 6638 (Option 3) © 2012 Elmdene International Ltd

PAK200072 Issue 02A August 2012