

MAXITEC



ELMDENE

*Security & Fire
Products*

Benefits:

Stylish External Sounder

Unique modern shape

Horizontal mounting

Choice of models including economic
Contractor model (Maxitec 500C)

Internal protection against harsh
environments for long life

'Engineer Friendly' for easy installation and
maintenance

Low current consumption

Economic multiple installations

Individual Cover logo can be supplied

Features:

- POLYCARBONATE COVER TRANSLUCENT
- ELECTRONICS ENCLOSED IN POLYCARBONATE OR METAL INNER COVER
- POLYCARBONATE OR METAL BACKPLATE
- DUAL PIEZO SOUNDERS
- TWIN LEDs (SELECTABLE)
- SINGLE PIEZO AND REDUCED FEATURE SET ON CONTRACTOR MODEL (Maxitec 500C)
- 15 MINUTE CUT-OFF TIMER (SELECTABLE)
- SAB FACILITY WITH ON-BOARD 6V NIMH BATTERY
- ENGINEER MODE FOR SILENT START-UP
- FRONT AND BACK TAMPERS
- OPTIONAL FOAM DETECTION
- SCREEN PRINTING AVAILABLE

*External Sounders
you can rely on*

www.elmdene.co.uk



INTRUDER



MAXITEC

Specifications

The Maxitec Range of external sirens feature a translucent coloured Polycarbonate outer cover fitted over a plastic or metal backplate. The electronics modules are protected by a polycarbonate inner cover and conformal coated to withstand harsh environments.

All Elmdene Sirens comply with the latest Regulations including

EN 50131-1

EN 61000-6-3

EN 50130-4

BS 4737

SPECIFICATION	MAX500M	MAX500	MAX500C
No of Piezos	2	2	1
Sound Output (dBA at 1m)	118	118	112
Operating Voltage (v dc Nominal)	10 – 14	10 – 14	10 – 14
Siren Operating Current Nominal	200mA	200mA	200mA
Strobe Current Nominal	100mA	100mA	100mA
Cut off timer	Selectable	Selectable	20 min or none
Twin LEDS	Selectable	Selectable	Fixed
Base Plate	Galvanised Steel (1.2mm)	Polycarbonate (3mm)	Polycarbonate (3mm)
Inner Cover	Galvanised Steel (1.2mm)	Polycarbonate (3mm)	ABS / Acrylic
Outer Cover	Polycarbonate (3mm)	Polycarbonate (3mm)	Polycarbonate (3mm)
Silent Engineer Mode	Yes	Yes	No
Replaceable Battery	Yes	Yes	Yes
Internal Battery	6v NiMH	6v NiMH	6v NiCd
Tamper Detection	Cover, Back, Module	Cover, Back, Module	Cover, Back
Siren & Strobe Trigger	Independent	Independent	Independent
Optional Foam Detection	Yes	Yes	No
Screen printing area	300 x 180 mm	300 x 180 mm	300 x 180 mm
External Dimensions	360w x 273 h x 78 d	360w x 273 h x 78 d	360w x 273 h x 78 d

ELMDENE INTERNATIONAL LIMITED
 Rodney Road, Fratton, Portsmouth PO4 8SS United Kingdom
 Tel: +44 (0)23 9273 9412 Fax: +44 (0)23 9281 1631
 e-mail: sales@elmdene.co.uk



ELMDENE

Security & Fire
 Products

www.elmdene.co.uk