

New for 2012!

TR Range 24V Door Retainer Power Supply Units

Product Overview

The enhanced Elmdene TR range of power supplies has been specifically designed for access control applications that require remote control of the power supply output. A typical example being where a TR power supply unit is used to power door retainers, with a link to the fire panel in order to switch off the output to the doors in the event of a fire alarm activation.

The units now have an expanded range of input options which includes the detection of a normally closed contact going open to provide a fully fail safe operation mode.

The three input options for remote control of the output are as follows:

- Opening of a normally closed volt-free contact
- Closing of a normally open volt-free contact
- Application of an external 24V dc supply such as a sounder circuit

LED status indicators provide quick diagnostics showing the presence of a mains input and output fuse failure.

Features

- Remote control of output
- Choice of switching options
- LED indication
- Mains transient protection
- Fail safe operation
- 3 year warranty

Compliance

CE Marked

Part Numbers

Part no	Description
TR2	2.0A
TR4	4.0A



TR Power Supply Unit

Technical Information

Output	22 – 30V dc nominal
Load output	2.0*, 4.0 A*
Mains supply	230V at 50Hz
Environment	-10°C to 40°C

**Not suitable for use with standby batteries*

Product Dimensions and Weight

H x W x D: Enclosure 200mm x 230mm x 80mm
Weight: TR2 3kg, TR4 3.5kg



ELMDENE
Protecting People & Property
A POTTER Company

Elmdene International Limited
3 Keel Close, Interchange Park,
Portsmouth, Hampshire, PO3 5QD, UK.

Tel: +44 (0)23 9269 6638
Fax: +44 (0)23 9266 0483
Email: sales@elmdene.co.uk

www.elmdene.co.uk

ELM0015-2011-Issue 1