

Quartz Sounders

Product Overview

The Quartz range of external sounders has been upgraded to fully meet the requirements of EN50131-4:2009 Grade 2 & 3, supporting the new functional and operational features now required.

The units are stylish and hard wearing. The outer cover and backplate are made of durable solid coloured polycarbonate.

The electronics module is fully enclosed and conformal coated to provide additional protection from harsh environments.

Features

- Designed to meet the requirements of EN50131-4:2009 Grade 2 and 3
- Unique, modern shape
- Environmental class IV
- Long working life
- Twin comfort LEDs
- Easy installation and maintenance
- Low current consumption, standby and alarm
- Replaceable internal battery
- Ring line monitoring (G3)
- Selectable cut-off timer
- Selectable SAB/SCB operation (G2)
- 24 hour self-test of battery and piezo (G3)
- Fault output (G3)
- Audible tamper tones for ease of commissioning (G3)
- Internal diagnostic LED (G3)
- Engineer mode for quiet installation (G3)
- Front and rear tamper detection
- Screen printing available
- 3 year warranty

Approvals & Certification

Quartz sounders meet the requirements of:

- PD6662: 2010
- EN50131-1: 2006
- EN50131-4: 2009
- EN61000-6-3



Quartz Sounder

Part Numbers

Part no	Grade	No of Piezos	Sound Output at 1M
Quartz 3000-G2	2	2	108dB(A)
Quartz 1000-G2		1	105dB(A)
Quartz 3000-G3	3	2	108dB(A)
Quartz 1000-G3		1	105dB(A)

Technical Information

Sound out (at 1m)	See table above
Operating voltage	9 – 15V dc

Product Dimensions

H x W x D: 292mm x 232mm x 68mm

