







APPROVED PSUS

Entire security and fire systems with all the advanced features that come with them rely on the power supply! Selecting a high-quality PSU built for reliability and longevity is the obvious choice.

Both EN and UL standards are highly credible. Compliance with these standards ensure products operate reliably and illustrate a manufacturer's dedication to safety and quality. Offering peace of mind when installing critical systems.



Boxed Power Supplies

Certified Fire, Access Control and Intruder PSUs are available within a choice of engineered enclosures to suit the application.

Unboxed Power Supplies

Compliant power modules to work within EN54 Fire systems and Certified UL294 power modules for Access Control systems.













EN54-4 certified power supplies for Fire alarm systems
EN12101-10 certified for "Smoke and Heat control systems"
UL294 certified units for Access Control systems
CE and UKCA mark









BOXED	APPROVAL	MODELS (HxWxD (mm))
	EN54-4 Certified power supplies for Fire detection and Fire alarm systems	\$\text{STX2401-T} 27.6Vdc, 1A. 300H \times 240W \times 60D Max battery 2 \times 12V 1.2Ah \text{STX2401-C} 27.6Vdc, 1A. 275H \times 330W \times 80D Max battery 2 \times 12V 7Ah \text{STX2402-C} 27.6Vdc, 2A. 275H \times 330W \times 80D Max battery 2 \times 12V 7Ah \text{STX2402-E} 27.6Vdc, 2A. 420H \times 400W \times 80D Max battery 2 \times 12V 17Ah \text{STX2405-C} 27.6Vdc, 5A. 275H \times 330W \times 80D Max battery 2 \times 12V 7Ah \text{STX2405-E} 27.6Vdc, 5A. 420H \times 400W \times 80D Max battery 2 \times 12V 17Ah \text{STX2410-E} 27.6Vdc, 10A. 420H \times 400W \times 80D Max battery 2 \times 12V 17Ah \text{STX2410-H} 27.6Vdc, 8A 420H \times 400W \times 180D Max \times battery 2 \times 12V 38Ah \text{STX2410-E} 27.6Vdc 7.2A 420H \times 400W \times 80D \text{HATT-BOX-65} 534H \times 465W \times 267D. Max battery 2 \times 12V 65Ah
	EN54-4 & EN12101-10 Certified for "Smoke and Heat control systems"	2401ST-C 27.6Vdc, 1A. 275H x 330W x 80D Max battery 2 x 12V 7Ah 2402ST-C 27.6Vdc, 2A. 275H x 330W x 80D Max battery 2 x 12V 7Ah 2402ST-E 27.6Vdc, 2A. 420H x 400W x 80D Max battery 2 x 12V 17Ah / 18Ah 2402ST-K 27.6Vdc, 2A. 325H x 350W x 105D Max battery 2 x 12V 12Ah 2402ST-H 27.6Vdc, 2A. 420H x 420W x 180D Max battery 2 x 12V 24Ah / 38Ah 2405ST-C 27.6Vdc, 5A. 275H x 330W x 80D Max battery 2 x 12V 7Ah 2405ST-E 27.6Vdc, 5A. 420H x 400W x 80D Max battery 2 x 12V 17Ah / 18Ah 2405ST-K 27.6Vdc, 5A. 325H x 350W x 105D Max battery 2 x 12V 12Ah 2405ST-H 27.6Vdc, 5A. 420H x 420W x 180D Max battery 2 x 12V 12Ah 2405ST-H 27.6Vdc, 5A. 420H x 420W x 180D Max battery 2 x 12V 24Ah / 38Ah + BATT-BOX-65 534H x 465W x 267D Max battery 2 x 12V 65Ah
	UL294 Certified units for Access Control systems	ACCESS-UL-PSU1 13.8Vdc, 4A. 440H x 250W x 115D, Max battery 12V 7Ah. Fits up to 2 door controllers. ACCESS-UL-PSU2 13.8Vdc, 4A. 505H x 407W x 80D, Max battery 12V 17Ah. Fits up to 4 door controllers. MULTI-ACCESS-UL-PSU6 13.8Vdc, 8A / 27.6Vdc 4A. 515H x 478W x 146D, Max battery 12V 17Ah. Fits up to 12 door controllers.
	EN50131-6 Certified power supplies for Intrusion and hold-up alarm systems	ENSO131-6 GRADE 2 GEN2-08-A 13.8Vdc, 1A. 200H × 230W × 80D, Max battery 12V 7Ah / 8Ah GEN2-08-B 13.8Vdc, 1A. 330H × 355W × 80D, Max battery 12V 7Ah / 8Ah GEN2-18-B 13.8Vdc, 1.5A. 330H × 355W × 80D, Max battery 12V 17Ah / 18Ah GEN2-18-C 13.8Vdc, 1.5A. 275H × 330W × 80D, Max battery 12V 17Ah / 18Ah ENSO131-6 GRADE 3 GEN3-08-A 13.8Vdc, 1A. 200H × 230W × 80D, Max battery 12V 7Ah / 8Ah GEN3-08-B 13.8Vdc, 1A. 330H × 355W × 80D, Max battery 12V 7Ah / 8Ah GEN3-08-C 13.8Vdc, 1A. 275H × 330W × 80D, Max battery 12V 7Ah / 8Ah GEN3-18-B 13.8Vdc, 1A. 330H × 355W × 80D, Max battery 12V 17Ah / 18Ah GEN3-18-B 13.8Vdc, 1.5A. 330H × 355W × 80D, Max battery 12V 17Ah / 18Ah GEN3-18-C 13.8Vdc, 1.5A. 275H × 330W × 80D, Max battery 12V 17Ah / 18Ah GEN3-34-R* 13.8Vdc, 3A. 410H × 390W × 80D, Max battery 2 × 12V / 17Ah *Meets the requirements of ENSO131-6

UNBOXED	APPROVAL	MODELS
	Compliant power modules for EN54 and EN12101-10 systems	EN54 STX2401-MOD 27.6Vdc, 1A STX2402-MOD 27.6Vdc, 2A STX2405-MOD 27.6Vdc, 5A STX2410-MOD 27.6Vdc, 10A EN54 & EN12101-10 2401ST-MOD 27.6Vdc, 1A 2402ST-MOD 27.6Vdc, 2A 2405ST-MOD 27.6Vdc, 5A
	UL294 Certified power modules for Access Control systems	UL294-12V4A-MOD 13.8Vdc, 4A UL294-12V8A-MOD 13.8Vdc, 8A

If you're looking for more personalised advice, don't hesitate to reach out to one of our experts and we'll be happy to assist.

Speak to one of our experts