



ELMDENE INTERNATIONAL LIMITED
 3 KEEL CLOSE
 INTERCHANGE PARK
 PORTSMOUTH
 HAMPSHIRE
 PO3 5QD, UK



Tel: +44 (0) 23 9269 6638
 Fax: +44 (0) 23 9266 0483
 Web: www.elmdene.co.uk

This product is designed to meet the requirement of EN50131-2-6:2008
Grade 2 and Environmental **Class III**.

Suitable for use in systems designed to comply with PD6662:2017

VS222 INSTALLATION INSTRUCTIONS

This 'HIGH SECURITY' sensor and magnet is supplied as a matched pair. Do not attempt to use the switch with any other magnet except as supplied or you may experience incompatibility problems. The magnet must be positioned with the coloured dot on the same side as the conduit exit from the switch. It will not work the other way around due to the biasing of the sensor reeds.

Always mount the switch/magnet assembly to have an air gap of around 10mm. The circuits may reset at less than 5mm separation.

The circuit diagram of the switch is classified as it is a high security device, and consequently, no circuit diagram or layout is published.

Six white wires are provided, the two for the tamper are not stripped, whilst the switched circuit is stripped for easy identification. The two circuits being of different lengths

PAK200080 Issue 05C VS222 Installation Instruction Sheet
 © 2019 Elmdene International Ltd

Feb 2019



ELMDENE INTERNATIONAL LIMITED
 3 KEEL CLOSE
 INTERCHANGE PARK
 PORTSMOUTH
 HAMPSHIRE
 PO3 5QD, UK



Tel: +44 (0) 23 9269 6638
 Fax: +44 (0) 23 9266 0483
 Web: www.elmdene.co.uk

This product is designed to meet the requirement of EN50131-2-6:2008
Grade 2 and Environmental **Class III**.

Suitable for use in systems designed to comply with PD6662:2017

VS222 INSTALLATION INSTRUCTIONS

This 'HIGH SECURITY' sensor and magnet is supplied as a matched pair. Do not attempt to use the switch with any other magnet except as supplied or you may experience incompatibility problems. The magnet must be positioned with the coloured dot on the same side as the conduit exit from the switch. It will not work the other way around due to the biasing of the sensor reeds.

Always mount the switch/magnet assembly to have an air gap of around 10mm. The circuits may reset at less than 5mm separation.

The circuit diagram of the switch is classified as it is a high security device, and consequently, no circuit diagram or layout is published.

Six white wires are provided, the two for the tamper are not stripped, whilst the switched circuit is stripped for easy identification. The two circuits being of different lengths

PAK200080 Issue 05C VS222 Installation Instruction Sheet
 © 2019 Elmdene International Ltd

Feb 2019



ELMDENE INTERNATIONAL LIMITED
 3 KEEL CLOSE
 INTERCHANGE PARK
 PORTSMOUTH
 HAMPSHIRE
 PO3 5QD, UK



Tel: +44 (0) 23 9269 6638
 Fax: +44 (0) 23 9266 0483
 Web: www.elmdene.co.uk

This product is designed to meet the requirement of EN50131-2-6:2008
Grade 2 and Environmental **Class III**.

Suitable for use in systems designed to comply with PD6662:2017

VS222 INSTALLATION INSTRUCTIONS

This 'HIGH SECURITY' sensor and magnet is supplied as a matched pair. Do not attempt to use the switch with any other magnet except as supplied or you may experience incompatibility problems. The magnet must be positioned with the coloured dot on the same side as the conduit exit from the switch. It will not work the other way around due to the biasing of the sensor reeds.

Always mount the switch/magnet assembly to have an air gap of around 10mm. The circuits may reset at less than 5mm separation.

The circuit diagram of the switch is classified as it is a high security device, and consequently, no circuit diagram or layout is published.

Six white wires are provided, the two for the tamper are not stripped, whilst the switched circuit is stripped for easy identification. The two circuits being of different lengths

PAK200080 Issue 05C VS222 Installation Instruction Sheet
 © 2019 Elmdene International Ltd

Aug 2019